

SECTION 1: Identification

1.1. Identification

Product form : Mixture
 Trade name : Patriot Chemical® PowerHouse
 Product code : 2706

1.2. Recommended use and restrictions on use

Recommended use : Laundry, Detergent

1.3. Supplier

Synthetic Labs
 24 Victory Lane
 Dracut, MA 01826 - United States
 T 800.255.4050 - F 978.957.5122

1.4. Emergency telephone number

Emergency number : 24 Hour Medical Emergency Number: 1-800-535-5053

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Skin corrosion/irritation Category 1A Causes severe skin burns and eye damage
 Serious eye damage/eye irritation Category 1 Causes serious eye damage

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger
 Hazard statements (GHS US) : Causes severe skin burns and eye damage
 Causes serious eye damage
 Precautionary statements (GHS US) : Do not breathe dust/fume/gas/mist/vapors/spray.
 Wash hands, forearms and face thoroughly after handling.
 Wear protective gloves/protective clothing/eye protection/face protection.
 If swallowed: rinse mouth. Do NOT induce vomiting
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
 If inhaled: Remove person to fresh air and keep comfortable for breathing
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 Immediately call a poison center or doctor
 Specific treatment (see supplemental first aid instruction on this label)
 Wash contaminated clothing before reuse.
 Store locked up.
 Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

Patriot Chemical® PowerHouse

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

3.2. Mixtures

| Name | Product identifier | % | GHS US classification |
|--------------------------|----------------------|---------|---|
| Sodium hydroxide | (CAS-No.) 1310-73-2 | 30 - 40 | Acute Tox. 1 (Oral), H300 Skin Corr. 1, H314 Eye Dam. 1, H318 |
| Nonylphenol, ethoxylated | (CAS-No.) 68412-54-4 | 5 - 10 | Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Irrit. 2, H319 |
| Potassium Hydroxide | (CAS-No.) 1310-58-3 | 1 - 5 | Met. Corr. 1, H290 Acute Tox. 4 (Oral), H302 Skin Corr. 1, H314 Eye Dam. 1, H318 |
| Sodium Tripolyphosphate | (CAS-No.) 7758-29-4 | 1 - 5 | Acute Tox. 2 (Inhalation:dust,mist), H330 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 |

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures general : Call a physician immediately.
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
- First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Call a physician immediately.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
- First-aid measures after ingestion : Rinse mouth. Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects after skin contact : Burns.
- Symptoms/effects after eye contact : Serious damage to eyes.
- Symptoms/effects after ingestion : Burns.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

No additional information available

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapors/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.

Other information : Dispose of materials or solid residues at an authorized site.

Patriot Chemical® PowerHouse

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapors/spray. Wear personal protective equipment.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| Potassium Hydroxide (1310-58-3) | | |
|---------------------------------------|-------------------------------------|----------------------|
| ACGIH | Local name | Potassium hydroxide |
| ACGIH | ACGIH Ceiling (mg/m ³) | 2 mg/m ³ |
| ACGIH | Remark (ACGIH) | URT, eye, & skin irr |
| Sodium hydroxide (1310-73-2) | | |
| ACGIH | Local name | Sodium hydroxide |
| ACGIH | ACGIH Ceiling (mg/m ³) | 2 mg/m ³ |
| ACGIH | Remark (ACGIH) | URT, eye, & skin irr |
| OSHA | OSHA PEL (TWA) (mg/m ³) | 2 mg/m ³ |
| Nonylphenol, ethoxylated (68412-54-4) | | |
| Not applicable | | |
| Sodium Tripolyphosphate (7758-29-4) | | |
| Not applicable | | |

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : Liquid.

Color : red

Odor : characteristic

Odor threshold : No data available

Patriot Chemical® PowerHouse

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | |
|---|-------------------------|
| pH | : 13.5 - 14 |
| pH solution | : ≥ 0 |
| Melting point | : Not applicable |
| Freezing point | : No data available |
| Boiling point | : No data available |
| Flash point | : No data available |
| Relative evaporation rate (butyl acetate=1) | : No data available |
| Flammability (solid, gas) | : Not applicable. |
| Vapor pressure | : No data available |
| Relative vapor density at 20 °C | : No data available |
| Relative density | : No data available |
| Specific gravity / density | : 1.08 g/m ³ |
| Solubility | : No data available |
| Log Pow | : No data available |
| Auto-ignition temperature | : No data available |
| Decomposition temperature | : No data available |
| Viscosity, kinematic | : No data available |
| Viscosity, dynamic | : No data available |
| Explosion limits | : No data available |
| Explosive properties | : No data available |
| Oxidizing properties | : No data available |

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

| | |
|-----------------------------|------------------|
| Acute toxicity (oral) | : Not classified |
| Acute toxicity (dermal) | : Not classified |
| Acute toxicity (inhalation) | : Not classified |

| Potassium Hydroxide (1310-58-3) | |
|---------------------------------------|--|
| LD50 oral rat | 333 mg/kg (Equivalent or similar to OECD 425, Rat, Male, Experimental value, Oral) |
| ATE US (oral) | 333 mg/kg body weight |
| Sodium hydroxide (1310-73-2) | |
| ATE US (oral) | 1.111 mg/kg body weight |
| Nonylphenol, ethoxylated (68412-54-4) | |
| LD50 oral rat | 1800 mg/kg (Rat) |
| LD50 dermal rabbit | 4400 mg/kg |

Patriot Chemical® PowerHouse

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| Nonylphenol, ethoxylated (68412-54-4) | |
|--|--|
| ATE US (oral) | 1800 mg/kg body weight |
| ATE US (dermal) | 4400 mg/kg body weight |
| Sodium Tripolyphosphate (7758-29-4) | |
| LD50 oral rat | > 2000 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s)) |
| LD50 dermal rabbit | > 4640 mg/kg body weight (24 h, Rabbit, Experimental value, Dermal, 14 day(s)) |
| LC50 inhalation rat (mg/l) | > 0.39 mg/l (EPA OPP 81-3: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (dust), 14 day(s)) |
| ATE US (dust, mist) | 0.05 mg/l/4h |

Skin corrosion/irritation : Causes severe skin burns and eye damage.
pH: 13.5 - 14

Serious eye damage/irritation : Causes serious eye damage.
pH: 13.5 - 14

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Specific target organ toxicity – single exposure : Not classified

Specific target organ toxicity – repeated exposure : Not classified

Aspiration hazard : Not classified

Viscosity, kinematic : No data available

Symptoms/effects after skin contact : Burns.

Symptoms/effects after eye contact : Serious damage to eyes.

Symptoms/effects after ingestion : Burns.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Before neutralisation, the product may represent a danger to aquatic organisms.

| Potassium Hydroxide (1310-58-3) | |
|--|---|
| LC50 fish 1 | 80 mg/l (96 h, Gambusia affinis, Static system, Fresh water, Experimental value) |
| Sodium hydroxide (1310-73-2) | |
| LC50 fish 1 | 45.4 mg/l (96 h, Salmo gairdneri, Static system, Fresh water, Experimental value, Solution >=50%) |
| EC50 Daphnia 1 | 40.4 mg/l (48 h, Ceriodaphnia sp., Experimental value, Nominal concentration) |
| Sodium Tripolyphosphate (7758-29-4) | |
| LC50 fish 1 | > 1850 mg/l (AFNOR, 24 h, Danio rerio, Fresh water, Experimental value) |
| EC50 Daphnia 1 | > 100 mg/l (EPA OTS 797.1930, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP) |
| ErC50 (algae) | 160 mg/l (ISO 8692, 4 day(s), Desmodesmus subspicatus, Fresh water, Experimental value) |

12.2. Persistence and degradability

| Potassium Hydroxide (1310-58-3) | |
|--|-----------------------------------|
| Persistence and degradability | Biodegradability: not applicable. |
| Chemical oxygen demand (COD) | Not applicable |
| ThOD | Not applicable |
| BOD (% of ThOD) | Not applicable |
| Sodium hydroxide (1310-73-2) | |
| Persistence and degradability | Biodegradability: not applicable. |
| Chemical oxygen demand (COD) | Not applicable (inorganic) |

Patriot Chemical® PowerHouse

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| Sodium hydroxide (1310-73-2) | |
|--|-------------------------------------|
| ThOD | Not applicable (inorganic) |
| Nonylphenol, ethoxylated (68412-54-4) | |
| Persistence and degradability | Not readily biodegradable in water. |
| Sodium Tripolyphosphate (7758-29-4) | |
| Persistence and degradability | Biodegradability: not applicable. |
| Chemical oxygen demand (COD) | Not applicable |
| ThOD | Not applicable |
| BOD (% of ThOD) | Not applicable |

12.3. Bioaccumulative potential

| Potassium Hydroxide (1310-58-3) | |
|--|----------------------------------|
| Bioaccumulative potential | Bioaccumulation: not applicable. |
| Sodium hydroxide (1310-73-2) | |
| Bioaccumulative potential | Not bioaccumulative. |
| Sodium Tripolyphosphate (7758-29-4) | |
| Bioaccumulative potential | Not bioaccumulative. |

12.4. Mobility in soil

| Sodium hydroxide (1310-73-2) | |
|--|---|
| Ecology - soil | No (test)data on mobility of the substance available. |
| Sodium Tripolyphosphate (7758-29-4) | |
| Log Koc | 2.15 (log Koc, Experimental value) |
| Ecology - soil | Low potential for adsorption in soil. |

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1760 Corrosive liquids, n.o.s. (Sodium Hydroxide,Potassium Hydroxide), 8, II
UN-No.(DOT) : UN1760
Proper Shipping Name (DOT) : Corrosive liquids, n.o.s.
Sodium Hydroxide,Potassium Hydroxide
Class (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136
Packing group (DOT) : II - Medium Danger
Hazard labels (DOT) : 8 - Corrosive



DOT Packaging Non Bulk (49 CFR 173.xxx) : 202
DOT Packaging Bulk (49 CFR 173.xxx) : 242
DOT Symbols : G - Identifies PSN requiring a technical name

Patriot Chemical® PowerHouse

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | |
|--|--|
| DOT Special Provisions (49 CFR 172.102) | : B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are not authorized. IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T11 - 6 178.274(d)(2) Normal..... 178.275(d)(3) TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively. TP27 - A portable tank having a minimum test pressure of 4 bar (400 kPa) may be used provided the calculated test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP. |
| DOT Packaging Exceptions (49 CFR 173.xxx) | : 154 |
| DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) | : 1 L |
| DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) | : 30 L |
| DOT Vessel Stowage Location | : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded. |
| DOT Vessel Stowage Other | : 40 - Stow "clear of living quarters" |
| Emergency Response Guide (ERG) Number | : 154 |
| Other information | : No supplementary information available. |

Transportation of Dangerous Goods

Not applicable

Transport by sea

| | |
|---------------------------------------|--|
| Transport document description (IMDG) | : UN 1760 CORROSIVE LIQUID, N.O.S., 8, II |
| UN-No. (IMDG) | : 1760 |
| Proper Shipping Name (IMDG) | : CORROSIVE LIQUID, N.O.S. |
| Class (IMDG) | : 8 - Corrosive substances |
| Packing group (IMDG) | : II - substances presenting medium danger |

Air transport

| | |
|---------------------------------------|---|
| Transport document description (IATA) | : UN 1760 Corrosive liquid, n.o.s., 8, II |
| UN-No. (IATA) | : 1760 |
| Proper Shipping Name (IATA) | : Corrosive liquid, n.o.s. |
| Class (IATA) | : 8 - Corrosives |
| Packing group (IATA) | : II - Medium Danger |

SECTION 15: Regulatory information

15.1. US Federal regulations

Potassium Hydroxide (1310-58-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Not subject to reporting requirements of the United States SARA Section 313

| | |
|-----------|---------|
| CERCLA RQ | 1000 lb |
|-----------|---------|

Sodium hydroxide (1310-73-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Not subject to reporting requirements of the United States SARA Section 313

| | |
|-----------|---------|
| CERCLA RQ | 1000 lb |
|-----------|---------|

Patriot Chemical® PowerHouse

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Nonylphenol, ethoxylated (68412-54-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

EPA TSCA Regulatory Flag

XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).

Sodium Tripolyphosphate (7758-29-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

Potassium Hydroxide (1310-58-3)

Listed on the Canadian DSL (Domestic Substances List)

Sodium hydroxide (1310-73-2)

Listed on the Canadian DSL (Domestic Substances List)

Nonylphenol, ethoxylated (68412-54-4)

Listed on the Canadian DSL (Domestic Substances List)

Sodium Tripolyphosphate (7758-29-4)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

| Component | State or local regulations |
|------------------------------------|--|
| Potassium Hydroxide(1310-58-3) | U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List |
| Sodium Tripolyphosphate(7758-29-4) | U.S. - Pennsylvania - RTK (Right to Know) List |
| Sodium hydroxide(1310-73-2) | U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List |

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 03/22/2017

Full text of H-phrases:

| | |
|------|---|
| H290 | May be corrosive to metals |
| H300 | Fatal if swallowed |
| H302 | Harmful if swallowed |
| H314 | Causes severe skin burns and eye damage |
| H315 | Causes skin irritation |
| H318 | Causes serious eye damage |
| H319 | Causes serious eye irritation |
| H330 | Fatal if inhaled |

Patriot Chemical® PowerHouse

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given

Flammability : 0 Minimal Hazard - Materials that will not burn

Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.